

ACCUSEIS SENSOR OPTION

FEATURES

- All-in-one single component recording unit with internal MEMS sensor
- Operated through INOVA's iX Studio command and control software
- Patented MEMS accelerometer and custom electronics to record P-wave data
- Offers flat amplitude and phase response over a wide frequency range
- Insensitivity to tilt-degradation enables faster deployment
- Automatic tilt correction and updating of measured tilt



GENERAL SPECIFICATIONS

No.of Digital Channels:	1
Data Storage Capacity:	16 GB non-volatile flash memory
Integrated Battery:	Rechargeable Li-ion
Battery Life:	23 days typical, 24 Hr operation
Wireless Communication:	Bluetooth LE, HyperQ
GPS:	L1-GPS /QZSS, GLONASS, BeiDou, Galileo
Timing Accuracy:	+/-20 μ s
Charging Temperature:	+5 °C to + 40°C
Operating Temperature:	-40 °C to + 70 °C
Water Immersion:	IP68

SENSOR SPECIFICATIONS

Digital Quantization:	24-bits
Sample Rate:	1 ms, 2 ms, or 4 ms
Time Standard:	Phase locked to GPS clock
Full Scale (Peak):	Normal Mode: 3.3 m/s ² (335mG) Large Signal Mode: 4.9 m/s ² (500mG)
Noise:	Normal Mode:0.3 μ m/s ² /VHz (30nG/VHz) 3 Hz to 400 Hz
Dynamic Range:	118 dB (normal mode)
Frequency response:	0 to 400 Hz
Digital High-Cut Filter:	0.82 Nyquist
Total Harmonic Distortion:	< -100 dB
Filter Options:	Minimum or Zero Phase

AUTOMATED TESTS

Unit temperature, sensor tilt, sensor noise, auto DC offset calibration, response accuracy test.